



ME260 Male Connector, Double Level Header with Flanges **DECA®**



ME260-381



ME260-500



DIMENSIONS/POSITIONS

| DIMENSIONS/POSITIONS | | ME260-381 | ME260-500 |
|----------------------|-----------------------|-------------------|-------------------|
| 間距 | Pitch | 3.81mm | 5.00mm |
| 位數 | Poles | 4 ~ 32Poles | 4 ~ 48Poles |
| 塑膠本體 | Housing Material | PBT | PA 66 |
| 焊針 | Pin Dimensions | Brass, Tin Plated | Brass, Tin Plated |
| PCB孔徑 | PCB Hole Diameter | 1.3mm | 1.5mm |
| 環境作業溫度 | Operating Temperature | -40°C to +105°C | -40°C to +105°C |

TECHNICAL DATA

| | | | |
|---|--------------------------------|------|------|
| 連接符合標準 Connection in acc. with standard EN-VDE | | | |
| 額定電流 I _n | Nominal Current I _n | 10A | 12A |
| 額定橫截面 | Nominal Cross Section | - | - |
| 最大負載電流 | Maximum load current | 10A | 12A |
| 絕緣材料 | Insulating Material | PBT | PA |
| 阻燃等級,符合UL94 Inflammability class acc. to UL94 | | V0 | V0 |
| 額定電壓,UL/CUL Nominal voltage, UL/CUL | | 300V | 300V |
| 額定電流,UL/CUL Nominal current, UL/CUL | | 10A | 16A |

