

MH150 PCB Terminal Block, High Power- Modular



DIMENSIONS/POSITIONS

MH150-635M

間距	Pitch	6.35mm
位數	Poles	2 ~ 8Poles
塑膠本體	Housing Material	PA 66
壓線圈	Cage Clamp	Steel, Zinc Plated
端子	Contact	Copper, Tin Plated
螺紋	Screw Thread	M3, Steel, Zinc Plated
電線線徑	Wire Size	8 ~ 18AWG
剝線長度	Wire Strip Length	6.5mm ~ 7.5mm
PCB孔徑	PCB Hole Diameter	1.6mm
最大緊固扭矩	Tightening Torque, Max.	9.0 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C

TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE		
額定電流 I_n	Nominal Current I_n	35A
額定橫截面	Nominal Cross Section	10mm ²
最大負載電流	Maximum load current	35A
絕緣材料	Insulating Material	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0
額定電壓,UL/CUL Nominal voltage, UL/CUL		600V
額定電流,UL/CUL Nominal current, UL/CUL		35A

