


# MH170 PCB Terminal Block, Modular



DIMENSIONS/POSITIONS		MH170-152	MH170-203
間距	Pitch	15.24mm	20.32mm
位數	Poles	2Poles	2Poles
塑膠本體	Housing Material	PA 66	PA 66
壓線圈	Cage Clamp	Steel, Zinc Plated	Steel, Zinc Plated
端子	Contact	Phosphor Bronze, Tin Plated	Phosphor Bronze, Tin Plated
螺紋	Screw Thread	M4, Stainless Strip Steel	M4, Stainless Strip Steel
電線線徑	Wire Size	6 ~ 20AWG	6 ~ 20AWG
PCB孔徑	PCB Hole Diameter	1.6mm	1.6mm
最大緊固扭矩	Tightening Torque, Max.	15.58 Lb-in	15.58 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

## TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE			
額定電流 I <sub>n</sub>	Nominal Current I <sub>n</sub>	65A	65A
額定橫截面	Nominal Cross Section	10mm <sup>2</sup>	10mm <sup>2</sup>
最大負載電流	Maximum load current	65A	65A
絕緣材料	Insulating Material	PA	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0	V0
額定電壓,UL/CUL Nominal voltage, UL/CUL		1000V	1000V
額定電流,UL/CUL Nominal current, UL/CUL		65A	65A

