


MPX315 PCB Spring Type Terminal Block



DIMENSIONS/POSITIONS

DIMENSIONS/POSITIONS		MPX315-100	MPX315-150
間距	Pitch	10.00mm	15.00mm
位數	Poles	2 ~ 8Poles	2 ~ 8Poles
塑膠本體	Housing Material	PA 66	PA 66
端子	Contact	Copper, Tin Plated	Copper, Tin Plated
彈片	Spring	Stainless Strip Steel	Stainless Strip Steel
抬起扭簧	Spring	Stainless Steel	Stainless Steel
端蓋	Cover	PA 66	PA 66
壓板	Lever	PA 66	PA 66
扣合件	Latch	PBT	PBT
扭簧	Spring	Stainless Steel	Stainless Steel
電線線徑	Wire Size	6 ~ 18AWG	4 ~ 18AWG
剝線長度	Wire Strip Length	17mm ~ 18mm	17mm ~ 18mm
PCB孔徑	PCB Hole Diameter	1.6mm	1.6mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE			
額定電流 I _n	Nominal Current I _n	76A	76A
額定橫截面	Nominal Cross Section	-	16mm ²
最大負載電流	Maximum load current	76A	76A
絕緣材料	Insulating Material	PA	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0	V0
額定電壓,UL/CUL Nominal voltage, UL/CUL		600V	600V
額定電流,UL/CUL Nominal current, UL/CUL		51A	66A

