


# MWX101 PCB Spring Type Terminal Block



## DIMENSIONS/POSITIONS

DIMENSIONS/POSITIONS		MWX101-750	MWX101-100
間距	Pitch	7.50mm	10.00mm
位數	Poles	2 ~ 20Poles	2 ~ 20Poles
塑膠本體	Housing Material	PA 66	PA 66
端蓋	Cover	PA 66	PA 66
端子	Contact	Brass, Tin Plated	Brass, Tin Plated
彈片	Spring	Stainless Strip Steel	Stainless Strip Steel
電線線徑	Wire Size	14 ~ 28AWG	14 ~ 28AWG
剝線長度	Wire Strip Length	5mm ~ 6mm	5mm ~ 6mm
PCB孔徑	PCB Hole Diameter	1.3mm	1.3mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

## TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE		
額定電流 I <sub>n</sub> Nominal Current I <sub>n</sub>	16A	16A
額定橫截面 Nominal Cross Section	-	-
最大負載電流 Maximum load current	16A	16A
絕緣材料 Insulating Material	PA	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94	V0	V0
額定電壓,UL/CUL Nominal voltage, UL/CUL	300V	300V
額定電流,UL/CUL Nominal current, UL/CUL	16A	16A

