


MWX200 PCB Spring Type Terminal Block



DIMENSIONS/POSITIONS

MWX200-762

| | | |
|--------|-----------------------|-----------------------|
| 間距 | Pitch | 7.62mm |
| 位數 | Poles | 2 ~ 20Poles |
| 塑膠本體 | Housing Material | PA 66 |
| 端蓋 | Cover | PA 66 |
| 端子 | Contact | Brass, Tin Plated |
| 彈片 | Spring | Stainless Strip Steel |
| 電線線徑 | Wire Size | 14 ~ 20AWG |
| 剝線長度 | Wire Strip Length | 9mm ~ 10mm |
| PCB孔徑 | PCB Hole Diameter | 1.2mm |
| 環境作業溫度 | Operating Temperature | -40°C to +105°C |

TECHNICAL DATA

| | | |
|---|--------------------------------|------|
| 連接符合標準 Connection in acc. with standard EN-VDE | | |
| 額定電流 I _n | Nominal Current I _n | 10A |
| 額定橫截面 | Nominal Cross Section | - |
| 最大負載電流 | Maximum load current | 10A |
| 絕緣材料 | Insulating Material | PA |
| 阻燃等級,符合UL94 Inflammability class acc. to UL94 | | V0 |
| 額定電壓,UL/CUL Nominal voltage, UL/CUL | | 300V |
| 額定電流,UL/CUL Nominal current, UL/CUL | | 10A |

