


# MWX220 PCB Spring Type Terminal Block



## DIMENSIONS/POSITIONS

## MWX220-500

|        |                       |                       |
|--------|-----------------------|-----------------------|
| 間距     | Pitch                 | 5.00mm                |
| 位數     | Poles                 | 2 ~ 99Poles           |
| 塑膠本體   | Housing Material      | PA 66                 |
| 端蓋     | Cover                 | PA 66                 |
| 端子     | Contact               | Copper, Tin Plated    |
| 彈片     | Spring                | Stainless Strip Steel |
| 電線線徑   | Wire Size             | 14 ~ 20AWG            |
| 剝線長度   | Wire Strip Length     | 9mm ~ 10mm            |
| PCB孔徑  | PCB Hole Diameter     | 1.2mm                 |
| 環境作業溫度 | Operating Temperature | -40°C to +105°C       |

## TECHNICAL DATA

|   |                                |      |
|---|--------------------------------|------|
| 連接符合標準<br>Connection in acc. with standard EN-VDE |                                |      |
| 額定電流 I <sub>n</sub>                               | Nominal Current I <sub>n</sub> | 10A  |
| 額定橫截面   | Nominal Cross Section          | -    |
| 最大負載電流  | Maximum load current           | 10A  |
| 絕緣材料  | Insulating Material            | PA   |
| 阻燃等級,符合UL94<br>Inflammability class acc. to UL94  |                                | V0   |
| 額定電壓,UL/CUL<br>Nominal voltage, UL/CUL            |                                | 300V |
| 額定電流,UL/CUL<br>Nominal current, UL/CUL            |                                | 10A  |

