


MWX302 PCB Spring Type Terminal Block



DIMENSIONS/POSITIONS

| DIMENSIONS/POSITIONS | | MWX302-100 | MWX302-016 |
|----------------------|-----------------------|-----------------------|-----------------------|
| 間距 | Pitch | 10.00mm | 10.16mm |
| 位數 | Poles | 2 ~ 24Poles | 2 ~ 24Poles |
| 塑膠本體 | Housing Material | PA 66 | PA 66 |
| 端蓋 | Cover | PA 66 | PA 66 |
| 端子 | Contact | Brass, Tin Plated | Brass, Tin Plated |
| 彈片 | Spring | Stainless Strip Steel | Stainless Strip Steel |
| 電線線徑 | Wire Size | 12 ~ 28AWG | 12 ~ 28AWG |
| 剝線長度 | Wire Strip Length | 5mm ~ 6mm | 5mm ~ 6mm |
| PCB孔徑 | PCB Hole Diameter | 1.3mm | 1.3mm |
| 環境作業溫度 | Operating Temperature | -40°C to +105°C | -40°C to +105°C |

TECHNICAL DATA

| | | | |
|---------------------|---|--------------------|--------------------|
| 連接符合標準 | Connection in acc. with standard EN-VDE | | |
| 額定電流 I _n | Nominal Current I _n | 20A | 20A |
| 額定橫截面 | Nominal Cross Section | 4.0mm ² | 4.0mm ² |
| 最大負載電流 | Maximum load current | 20A | 20A |
| 絕緣材料 | Insulating Material | PA | PA |
| 阻燃等級,符合UL94 | Inflammability class acc. to UL94 | V0 | V0 |
| 額定電壓,UL/CUL | Nominal voltage, UL/CUL | 300V | 300V |
| 額定電流,UL/CUL | Nominal current, UL/CUL | 20A | 20A |

