




CDU 2.5 SL



CDU 4



CDU 4 SL



Specifications (產品規格)	2.5 mm ²		4 mm ²		4 mm ²	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	600V/24A/AWG 10-22		UL [®] 600 V/35 A/AWG 8-22		600 V/35 A/AWG 8-22	
CSA	600V/24A/AWG 10-22		600 V/35 A/AWG 8-22		600 V/35 A/AWG 8-22	
IEC	800V/24A/0.5-2.5mm ²		800 V/32 A/0.5-4mm ²		500V/32A/0.5-4mm ²	
Insulating impulse voltage withstand / Pollution degree (額定衝擊電壓 / 污染等級)	8KV / 3		8KV / 3		8KV / 3	
Torque (lb-in) (扭緊力矩)	7		7.7		7.7	
Clamping Screw (M) (螺絲)	M3		M3		M3	
Insulation stripping length(mm) (剝線長度)	10-12 mm		10-12 mm		10-12 mm	
Material/Available Color (材質顏色)						
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
For TS35x7.5	5/60/47.5		6 x 60 x 47.5		6 x 60 x 47.5	
For TS35x15	5/60/55		6 x 60 x 55		6 x 60 x 55	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板)	SEW35	50	SEW35	50	SEW35	50
	CEW35/2	50	CEW35/2	50	CEW35/2	50
End Plate (擋板)	CEP 1	50	CEP 1	50	CEP 1	50
Partition (擋板/隔片)	CEP 5	50	CEP 5	50	CEP 5	50
Cross Jumper (中心式聯接件)	CQV 2.5/2	50	CQV 4/2	50	CQV 4/2	50
	CQV 2.5/3	50	CQV 4/3	50	CQV 4/3	50
	CQV 2.5/4	50	CQV 4/4	50	CQV 4/4	50
	CQV 2.5/10	20	CQV 4/10	20	CQV 4/10	20
	CQB 2.5/2	50	CQB 4/2	50	CQB 4/2	50
Comb Link (邊接式聯接件)	CQB 2.5/3	50	CQB 4/3	50	CQB 4/3	50
	CQB 2.5/10	20	CQB 4/10	20	CQB 4/10	20
	WS-2.5	50	WS-4	50	WS-4	50
Warning Cover (安全標示蓋)	WS-2.5	50	WS-4	50	WS-4	50
Marking Tags (標記號)	W5 W5Z W5K	500	W6 W6Z W6K	500	W6 W6Z W6K	500
	W7 W7Z W7K	400	W8 W8Z W8K	400	W8 W8Z W8K	400
Test plug (測試插頭)	TPS2.0 (Ø2.0)	20	TPS2.3 (Ø2.3)	20	TPS2.3 (Ø2.3)	20
	TPS2.3 (Ø2.3)	20				
Socket (測試插孔)	TP2.0	50	TP2.3	50	TP2.3	50
	TP2.3	50				
Protection Cover (防觸蓋)	DP1	20	DP1	20	DP1	20
Retaining Plates (中界板)	AD1	50	AD1	50	AD1	50
Tool (工具)	DS3		DS3		DS3	