

CDU 50



CDU 95



CDU 150



Specifications (產品規格)	50 mm ²	95 mm ²	150 mm ²
Technical Data (技術參數)	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size
UL	c us 1000 V / 150 A / AWG 1/0-6	c us 1000 V / 230 A / AWG 4/0-2	600V/275A/AWG 2-300
CSA	1000 V / 150 A / AWG 1/0-6	1000 V / 230 A / AWG 4/0-2	600V/275A/AWG 2-300
IEC	1000V/150A/16-50 mm ²	1000V/232A/35-95 mm ²	1000V/309A/35-150mm ²
Insulating impulse voltage withstand (額定衝擊電壓 / 污染等級) /Pollution degree	8KV / 3	8KV / 3	8KV / 3
Torque (lb-in) (扭緊力矩)	53	150	165
Clamping Screw (M) (螺絲)	M6	M8	M10
Insulation stripping length(mm) (剝線長度)	25-30 mm	30-35 mm	30-40 mm
Material/Available Color (材質顏色)			
Rail Dimensions (導軌尺寸)	T / W / H (mm)	T / W / H (mm)	T / W / H (mm)
For TS35x7.5	20 x 70.5 x 76	25 x 80 x 90	31x93x109
For TS35x15	20 x 70.5 x 83.5	25 x 80 x 97.5	31x93x116.5
Accessories (附件)	Cat. No. Qty.	Cat. No. Qty.	Cat. No. Qty.
End Bracket (終端擋板)	SEW35 50 CEW35/1 50	SEW35 50 CEW35/1 50	CEW35/1 50
End Plate (擋板)			
Partition (擋板/隔片)			
Cross Jumper (中心式聯接件)	CQV 50/2 50 CQV 50/3 50		
Comb Link (邊接式聯接件)	CQB-50/2 50 CQB-50/3 50	CQB-95/2 50 CQB-95/3 50	CQB150/2 50
Warning Cover (安全標示蓋)			
Marking Tags (標記號)	W6 W6Z W6K 500 W8 W8Z W8K 400	W6 W6Z W6K 500 W8 W8Z W8K 400	W6 W6Z W6K 500 W8 W8Z W8K 500
Test plug (測試插頭)			
Socket (測試插孔)			
Protection Cover (防觸蓋)			
Retaining Plates (中界板)			
Tool (工具)	DK5	DK6	DK8