




CDU 2.5/3N

CDU 2.5/4N

CDU 4 N



Specifications (產品規格)	2.5 mm ²		2.5 mm ²		4 mm ²	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	300V/20A/AWG 12-24		300V/20A/AWG 12-24		cUL [®] 600 V / 30 A / AWG 10-22	
CSA	300V/20A/AWG 12-24		300V/20A/AWG 12-24		600 V / 30 A / AWG 10-22	
IEC	400V/24A/0.2-2.5mm ²		400V/24A/0.2-2.5mm ²		800V/32A/0.5-4mm ²	
Insulating impulse voltage withstand / Pollution degree (額定衝擊電壓 / 污染等級)	6KV / 3		6KV / 3		8KV / 3	
Torque (lb-in) (扭緊力矩)	5		5		7.7	
Clamping Screw (M) (螺絲)	M2.6		M2.6		M3	
Insulation stripping length(mm) (剝線長度)	8 mm		8 mm		8-10 mm	
Material/Available Color (材質顏色)						
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
For TS35x7.5	5.2/50.5/47		5.2/63.5/47		6x42.5x47	
For TS35x15	5.2/50.5/54.5		5.2/63.5/54.5		6x42.5x54.5	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板)	CEW35/2	50	CEW35/2	50	SEW35	50
	SEW35	50	SEW35	50	CEW35/2	50
End Plate (擋板)	CDU2.5/3-C	50	CDU2.5/4-C	50	CEP 6	50
Partition (擋板/隔片)	-	50	-	50	CEP 6	50
Cross Jumper (中心式聯接件)		50		50	CQV 4/2	50
	CQVM2.5/2	50	CQVM2.5/2	50	CQV 4/3	50
		50		50	CQV 4/4	50
		20		20	CQV 4/10	20
		50		50	CQB 4/2	50
Comb Link (邊接式聯接件)	CQB2.5/2	50	CQB2.5/2	50	CQB 4/3	50
		20		20	CQB 4/10	20
		50		50	WSS4	50
Warning Cover (安全標示蓋)	-	50	-	50		
Marking Tags (標記號)	W5	500	W5	500	W6 W6Z W6K	500
Test plug (測試插頭)	-	20	-	20	TPS2.3 (Ø2.3)	20
Socket (測試插孔)	-	50	-	50	TP2.3	50
Protection Cover (防觸蓋)	-	20	-	20	DP1	20
Retaining Plates (中隔板)	-	50	-	50	AD1	50
Tool (工具)	DS3		DS3		DS3	