




### CPE 95

### CPE 2.5N

### CPE 2.5/3N



Specifications (產品規格)	95 mm <sup>2</sup>		2.5 mm <sup>2</sup>		2.5 mm <sup>2</sup>	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	c  US AWG 4/0-2		AWG 12-26		AWG 12-24	
CSA	AWG 4/0-2		AWG 12-26		AWG 12-24	
IEC	35-95mm <sup>2</sup>		0.2-2.5mm <sup>2</sup>		0.2-2.5mm <sup>2</sup>	
Insulating impulse voltage withstand (額定衝擊電壓/Pollution degree /污染等級)	8KV / 3		8KV / 3		6KV / 3	
Torque (lb-in) (扭緊力矩)	90		7		7	
Clamping Screw (M) (螺絲)	M8		M3		M2.6	
Insulation stripping length(mm) (剝線長度)	30-35 mm		10-14 mm		8 mm	
Material/Available Color (材質顏色)						
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
For TS35x7.5	25 x 80 x 90		5 x 42.5 x 47.5		5.2x50.5x47	
For TS35x15	25 x 80 x 97.5		5 x 57 x 55		5.2x50.5x54.5	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板)	SEW35	50	SEW35	50	CEW35/2	50
	CEW35/1	50	CEW35/2	50	SEW35	50
Comb Link (邊接式聯接件)	CQB 95/2	50	CQB 2.5/2	50	CQB2.5/2	50
	CQB 95/3	50	CQB 2.5/3	50		
			CQB 2.5/10	20		
Marking Tags (標記號)	W6 W6Z W6K	500	W5 W5Z W5K	500	W5 W5Z W5K	500
	W8 W8Z W8K	400	W7 W7Z W7K	400		
Protection Cover (防觸蓋)			DP1	20		
Retaining Plates (中界板)			AD1	50		
Tool (工具)	DS6 DS8		DS3		DS3	