




CDK 4V



CDK 6V



CDK 10V



Specifications (產品規格)	4 mm ²	6 mm ²	10 mm ²
Technical Data (技術參數)	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size
UL	600 V/30 A/AWG 10-22	600 V/41 A/AWG 8-20	600 V/65 A/AWG 6-16
CSA	600 V/30 A/AWG 10-22	600 V/41 A/AWG 8-20	600 V/65 A/AWG 6-16
IEC	800V/32A/0.5-4mm ²	500V/50A/0.5-6mm ²	500V/76A/1.5-10mm ²
Insulating impulse voltage withstand /Pollution degree (額定衝擊電壓 /污染等級)	6KV / 3	8KV / 3	8KV / 3
Torque (lb-in) (扭緊力矩)	8	14	19
Clamping Screw (M) (螺絲)	M3	M4	M4
Insulation stripping length(mm) (剝線長度)	6 mm	10-12 mm	10-12 mm
Material/Available Color (材質顏色)			
Rail Dimensions (導軌尺寸)	T / W / H (mm)	T / W / H (mm)	T / W / H (mm)
For TS35x7.5	6 x 69 x 63.5	8 x 69 x 73	10 x 69 x 73
For TS35x15	6 x 69 x 71	8 x 69 x 80.5	10 x 69 x 80.5
Accessories (附件)	Cat. No. Qty.	Cat. No. Qty.	Cat. No. Qty.
End Bracket (終端擋板)	CEW35/2 50 SEW35 50	CEW35/2 50 SEW35 50	CEW35/2 50 SEW35 50
End Plate (擋板)	CEP3 50	CEP4 50	CEP4 50
Cross Jumper (中心式聯接件)	CQV4/2 50	CQV6/2 50	CQV10/2 50
	CQV4/3 50	CQV6/3 50	CQV10/3 50
	CQV4/4 50	CQV6/4 50	CQV10/4 50
Comb Link (邊接式聯接件)	CQB4/2 50	CQB6/2 50	CQB10/2 50
	CQB4/3 50	CQB6/3 50	CQB10/3 50
	CQB4/4 20	CQB6/4 20	CQB10/4 20
Warning Cover (安全標示蓋)	W5 W5Z W5K 500	W6 W6Z W6K 500	W6 W6Z W6K 500
Marking Tags (標記號)			
Protection Cover (防觸蓋)	DP1 20		
Retaining Plates (中界板)			DS4
Tool (工具)	DS3	DS4	DS4