




CTR 4



CTR 6



CTR 10



Specifications (產品規格)	4 mm ²	6 mm ²	10 mm ²
Technical Data (技術參數)	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size
UL	UL _{us} 600 V/22 A/AWG 10-22	600 V/ 24A/AWG 8-22	600 V/ 40A/AWG 6-22
CSA	600 V/22 A/AWG 10-22	600 V/ 24A/AWG 8-22	600 V/ 40A/AWG 6-22
IEC	800 V/22 A/0.5-4mm ²	630V / 24A / 0.5-6mm ²	630 V/40 A/1.5-10mm ²
Insulating impulse voltage withstand (額定衝擊電壓 / Pollution degree / 污染等級)	6KV / 3	8KV / 3	8KV / 3
Torque (lb-in) (扭緊力矩)	6	14	19
Clamping Screw (M) (螺絲)	M3	M4	M4
Insulation stripping length(mm) (剝線長度)	10-12 mm	12-14 mm	12-14 mm
Material/Available Color (材質顏色)			
Rail Dimensions (導軌尺寸)	T / W / H (mm)	T / W / H (mm)	T / W / H (mm)
For TS35x7.5	6x 60 x 47.5	8 x 60 x 47.5	10x 60 x 47.5
For TS35x15	6 x 60 x 55	8 x 60 x 55	10 x 60 x 55
Accessories (附件)	Cat. No. Qty.	Cat. No. Qty.	Cat. No. Qty.
End Bracket (終端擋板)	SEW35 50 CEW35/2 50	SEW35 50 CEW35/2 50	SEW35 50 CEW35/2 50
End Plate (擋板)	CEP 1 50	CEP 5 50	CEP 5 50
Partition (擋板/隔片)	CEP 5 50		
Comb Link (邊接式聯接件)	CQB 4/2 50	CQB 6/2 50	CQB 10/2 50
	CQB 4/3 50	CQB 6/3 50	CQB 10/3 50
	CQB 4/10 20	CQB 6/10 20	CQB 10/10 20
Marking Tags (標記號)	W6 W6Z W6K 500 W8 W8Z W8K 400	W6 W6Z W6K 500 W8 W8Z W8K 400	W6 W6Z W6K 500 W8 W8Z W8K 400
Test plug (測試插頭)	-	-	-
Socket (測試插孔)	-	-	-
Diode Plug (二極體插頭)	+ - CSD4 25	CSD6 25	CSD10 25
	- + CSD4 25	CSD6 25	CSD10 25
LED Fuse Type (顯示型保險絲插座) Insert	CSI4 25	CSI6 25	CSI10 25
Protection Cover (防觸蓋)	DP1 20	DP1 20	DP1 20
Retaining Plates (中界板)	AD1 50	AD1 50	AD1 50
Tool (工具)	DS3	DS4	DS4