





CTR 4/4



CTR 10SF



Specifications (產品規格)	4 mm ²		
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		
UL	600 V / 12 A / AWG 10-22		
CSA	600 V / 12 A / AWG 10-22		
IEC	800 V / 32 A / 0.5-4mm ²		
Insulating impulse voltage withstand (額定衝擊電壓 / Pollution degree / 污染等級)	6KV / 3		
Torque (lb-in) (扭緊力矩)	7		
Clamping Screw (M) (螺絲)	M3		
Insulation stripping length(mm) (剝線長度)	9-10 mm		
Material/Available Color (材質顏色)			
Rail Dimensions (導軌尺寸)	T / W / H (mm)		
For TS35x7.5	6 X 66 X 50.5		
For TS35x15	6 X 66 X 58		
Accessories (附件)	Cat. No.	Qty.	
End Bracket (終端擋板)	SEW35	50	
	CEW35/2	50	
End Plate (擋板)	CTR 4/4C	50	
Partition (擋板/隔片)	CEP 5	50	
	CQB 4/2	50	
Comb Link (邊接式聯接件)	CQB 4/3	50	
	CQB 4/10	20	
MarkingTags (標記號)	W6 W6Z W6K	500	
Test plug (測試插頭)	-	-	
Socket (測試插孔)	-	-	
Diode Plug (二極體插頭)	+ -	CSD4	25
	- +	CSD4	25
LED Fuse Type (顯示型保險絲插座) Insert	CSI4	25	
Protection Cover (防觸蓋)	DP1	20	
Retaining Plates (中界板)	AD1	50	
Tool (工具)	DS3		

Specifications (產品規格)	10 mm ²	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size	
UL	600 V / 6.3 A / AWG 6-22	
CSA	600 V / 6.3 A / AWG 6-22	
IEC	660 V / 6.3 A / 1.5-10mm ²	
Insulating impulse voltage withstand (額定衝擊電壓 / Pollution degree / 污染等級)	8KV / 3	
Torque (lb-in) (扭緊力矩)	19	
Clamping Screw (M) (螺絲)	M4	
Insulation stripping length(mm) (剝線長度)	12-14 mm	
Material/Available Color (材質顏色)		
Rail Dimensions (導軌尺寸)	T / W / H (mm)	
For TS35x7.5	12 X 61.6 X 47.5	
For TS35x15	12 X 61.6 X 55	
Accessories (附件)	Cat. No.	Qty.
End Bracket (終端擋板)	SEW35	50
	CEW35/2	50
End Plate (擋板)	CTR 10SF-C	50
Partition (擋板/隔片)	CQV 10/2	50
	CQV 10/3	50
	CQV 10/4	20
Comb Link (邊接式聯接件)	CQB 10/2	50
	CQB 10/3	50
	CQB 10/10	20
MarkingTags (標記號)	-	-
Test plug (測試插頭)	-	-
Socket (測試插孔)	-	-
Tool (工具)	DS4	