




CTR 4SB



CTR 4SF



Specifications (產品規格)	4 mm ²	4 mm ²
Technical Data (技術參數)	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size
UL	c us 600 V / 16A/AWG 12-22	c us 600 V / 15A/AWG 14-22
CSA	600 V / 16A/AWG 12-22	600 V / 15A/AWG 14-22
IEC	800 V / 10A /0.5-4mm ²	800 V / 10A /0.5-4mm ²
Insulating impulse voltage withstand /Pollution degree (額定衝擊電壓 /污染等級)	6KV / 3	6KV / 3
Torque (lb-in) (扭緊力矩)	6	6
Clamping Screw (M) (螺絲)	M3	M3
Insulation stripping length(mm) (剝線長度)	10-12mm	10-12mm
Material/Available Color (材質顏色)		
Rail Dimensions (導軌尺寸)	T / W / H (mm)	T / W / H (mm)
For TS35x7.5	8 x 60 x 54.5	8 x 60 x 54.5
For TS35x15	8 x 60 x 62	8 x 60 x 62
Accessories (附件)	Cat. No. Qty.	Cat. No. Qty.
End Bracket (終端擋板)	SEW 35 50 CEW 35/2 50	SEW 35 50 CEW 35/2 50
End Plate (擋板)	CEP 5 50	CEP 5 50
Partition (擋板/隔片)		
Comb Link (邊接式聯接件)	CQB 6/2 50 CQB 6/3 50 CQB 6/10 50	CQB 6/2 50 CQB 6/3 50 CQB 6/10 50
MarkingTags (標記號)	W6 W6Z W6K 500 W8 W8Z W8K 500	W6 W6Z W6K 500 W8 W8Z W8K 500
Test plug (測試插頭)	-	-
Socket (測試插孔)	-	-
Diode Plug (二極體插頭)	+ - CSD4 25 - + CSD4 25	CSD4 25 CSD4 25
LED Fuse Type (顯示型保險絲插座) Insert	+ - CSI4 25	CSI4 25
Protection Cover (防觸蓋)	-	-
Retaining Plates (中界板)	-	-
Tool (工具)	DS3	DS3