





SDU 1.5/3








SDU 1.5/4



SDU 2.5



Specifications (產品規格)	1.5 mm <sup>2</sup>	1.5 mm <sup>2</sup>	2.5 mm <sup>2</sup>
<b>Technical Data (技術參數)</b>	<b>Rated voltage/Rated current/Wire size</b>	<b>Rated voltage/Rated current/Wire size</b>	<b>Rated voltage/Rated current/Wire size</b>
UL	600V/10A/AWG 16-28	600V/10A/AWG 16-28	 600V/18A/AWG 12-28
CSA	600V/10A/AWG 16-28	600V/10A/AWG 16-28	600V/18A/AWG 12-28
IEC	800V/17.5A/0.2~1.5mm <sup>2</sup>	800V/17.5A/0.2~1.5mm <sup>2</sup>	 800V/24A/0.2~2.5mm <sup>2</sup>
Insulating impulse voltage withstand (額定衝擊電壓/Pollution degree /污染等級)	8KV / 3	8KV / 3	8KV / 3
Insulation stripping length(mm) (剝線長度)	8-9mm	8-9mm	8-9 mm
Material/Available Color (材質顏色)			
<b>Rail Dimensions (導軌尺寸)</b>	<b>T / W / H (mm)</b>	<b>T / W / H (mm)</b>	<b>T / W / H (mm)</b>
For TS35x7.5 	4x62.5x34.5	4x73x34.5	5 x 53 x 35.5
For TS35x15 	4x62.5x42	4x73x42	5 x 53 x 43
<b>Accessories (附件)</b>	<b>Cat. No.</b> <b>Qty.</b>	<b>Cat. No.</b> <b>Qty.</b>	<b>Cat. No.</b> <b>Qty.</b>
End Bracket (終端擋板) 	SEW35 50	SEW35 50	SEW35 50
End Plate (擋板) 	SEP16 50	SEP17 50	SEP 1 50
Comb Link (連接式聯接件) 	SQV1.5/2 50	SQV1.5/2 50	SQV 2.5/2 50
	SQV1.5/3 50	SQV1.5/3 50	SQV 2.5/3 50
	SQV1.5/4 50	SQV1.5/4 50	
MarkingTags (標記號) 	W3 W3Z W3K 500	W3 W3Z W3K 500	W5 W4Z W4K 500
Tool (工具) 	DS2	DS2	DS3