




SDU 6/3



SDU 10



SDU 10/3



Specifications (產品規格)	6 mm ²	10 mm ²	10 mm ²
Technical Data (技術參數)	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size
UL	600V/30A/AWG 10-24	600V/38A/AWG 8-24	600V/38A/AWG 8-24
CSA	600V/30A/AWG 10-24	600V/38A/AWG 8-24	600V/38A/AWG 8-24
IEC	800V/41A/0.2~6mm ²	800V/57A/0.2~10mm ²	800V/57A/0.2~10mm ²
Insulating impulse voltage withstand (額定衝擊電壓/Pollution degree /污染等級)	8KV / 3	8KV / 3	8KV / 3
Insulation stripping length(mm) (剝線長度)	12-13 mm	15-16 mm	15-16 mm
Material/Available Color (材質顏色)			
Rail Dimensions (導軌尺寸)	T / W / H (mm)	T / W / H (mm)	T / W / H (mm)
For TS35x7.5	8 x 93 x 40	10 x 78 x 42.5	10 x 97.5 x 42.5
For TS35x15	8 x 93 x 47.5	10 x 78 x 50	10 x 97.5 x 50
Accessories (附件)	Cat. No. Qty.	Cat. No. Qty.	Cat. No. Qty.
End Bracket (終端擋板)	SEW35 50	SEW35 50	SEW35 50
End Plate (擋板)	SEP 8 50	SEP 9 50	SEP 10 50
Comb Link (連接式聯接件)	SQV 6/2 50	SQV 10/2 50	SQV 10/2 50
	SQV 6/3 50	SQV 10/3 50	SQV 10/3 50
MarkingTags (標記號)	W6 W6Z W6K 500	W6 W6Z W6K 500	W6 W6Z W6K 500
Tool (工具)	DS4	DS5	DS5