




SDU 16/3














SDU 35



SDK 2.5



Specifications (產品規格)	16 mm ²	35 mm ²	2.5 mm ²
Technical Data (技術參數)	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size
UL	600V/65A/AWG 4-16	600V/120A/AWG 2-12	 600V/20A/AWG 12-28
CSA	600V/65A/AWG 4-16	600V/120A/AWG 2-12	600V/20A/AWG 12-28
IEC	800V/76A/1.5~16mm ²	800V/125A/2.5~35mm ²	800V/24A/0.2~2.5mm ²
Insulating impulse voltage withstand (額定衝擊電壓/Pollution degree /污染等級)	8KV / 3	8KV / 3	8KV / 3
Insulation stripping length(mm) (剝線長度)	16-17mm	25mm	8-9 mm
Material/Available Color (材質顏色)			
Rail Dimensions (導軌尺寸)	T / W / H (mm)	T / W / H (mm)	T / W / H (mm)
For TS35x7.5 	12.2x107.8x51	16x100x59	5x75.5x44.5
For TS35x15 	12.2x107.8x58.5	16x100x66.5	5x75.5x52
Accessories (附件)	Cat. No. Qty.	Cat. No. Qty.	Cat. No. Qty.
End Bracket (終端擋板) 	SEW35 50	SEW35 50	SEW35 50
End Plate (擋板) 	SEP13 50	SEP14 50	SEP 11 50
Comb Link (連接式聯接件) 	SQV16/2 50	SQV35/2 50	SQV 2.5/2 50 SQV 2.5/3 50
MarkingTags (標記號) 	W6 W6Z W6K 500	W6 W6Z W6K 500	W5 W5Z W5K 500
Tool (工具) 	DS5	DS6	DS3