



### SDUNB 2.5/2



### SDUNS 2.5



### SDUNS 2.5/2



Specifications (產品規格)	2.5 mm <sup>2</sup>		2.5 mm <sup>2</sup>		2.5 mm <sup>2</sup>	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	600V/15A/AWG28-12		c  600V/15A/AWG28-12		600V/15A/AWG28-12	
CSA	600V/15A/AWG28-12		600V/15A/AWG28-12		600V/15A/AWG28-12	
IEC	800V/24A/0.2-2.5 mm <sup>2</sup>		800V/24A/0.2-2.5 mm <sup>2</sup>		800V/24A/0.2-2.5 mm <sup>2</sup>	
Insulating impulse voltage withstand (額定衝擊電壓/Pollution degree /污染等級)	8KV / 3		8KV / 3		8KV / 3	
Insulation stripping length(mm) (剝線長度)	10-12mm		10-12mm		10-12mm	
Material/Available Color (材質顏色)						
Dimensions (外形尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
	10x22.2x32.2		6x22.2x32.2		10x22.2x32.2	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
Terminal Strip (中間端子)	SDUNS2.5-B	25	SDUNS2.5-A	25	SDUNS2.5-A	25
	SDUNB2.5-B	25	SDUNS2.5-B	25	SDUNS2.5-B	25
	SDUNB2.5/2-B	25	SDUNS2.5/2-B	25	SDUNS2.5/2-B	25
	SDUNS2.5/2-A	25				
End Bracket (終端擋板)	SDUNB2.5-C	25	SDUNS2.5-C	25	SDUNS2.5-C	25
Comb Link (邊接式聯接件)						
Marking Tags (標記號)	W5 W5Z W5K	500	W6 W6Z W6K	500	W5 W5Z W5K	500
End Plate (擋板)						
Tool (工具)	DS3		DS3		DS3	