





SDUS 1.5/2













SDUS 2.5



SDUS 2.5/2



Specifications (產品規格)	1.5 mm ²	2.5 mm ²	2.5 mm ²
Technical Data (技術參數)	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size	Rated voltage/Rated current/Wire size
UL	300V/10A/AWG28-16	 300V/15A/AWG28-14	300V/15A/AWG28-14
CSA	300V/10A/AWG28-16	300V/15A/AWG28-14	300V/15A/AWG28-14
IEC	400V/17.5A/0.2-1.5 mm ²	 500V/24A/0.2-2.5 mm ²	500V/24A/0.2-2.5 mm ²
Insulating impulse voltage withstand (額定衝擊電壓/Pollution degree 污染等級)	8KV / 3	8KV / 3	8KV / 3
Insulation stripping length(mm) (剝線長度)	8-10mm	8-10mm	8-10mm
Material/Available Color (材質顏色)			
Dimensions (外形尺寸)	T / W / H (mm)	T / W / H (mm)	T / W / H (mm)
	8x25x17	6x28x18	10x28x18
Accessories (附件)	Cat. No. Qty.	Cat. No. Qty.	Cat. No. Qty.
Central Terminals (中間端子) 	SDUB 1.5-B 25	SDUB 2.5-B 25	SDUB 2.5-B 25
	SDUB 1.5/2-B 25	SDUB 2.5/2-B 25	SDUB 2.5/2-B 25
End Bracket (擋板) 	SDUB 1.5-C 25	SDUB 2.5-C 25	SDUB 2.5-C 25
Comb Link (邊接式聯接件) 	SQB 1.5 25	SQB 2.5 25	SQB 2.5 25
Lever (壓板) 	SDUB 1.5-D 25	SDUB 2.5-D 25	SDUB 2.5-D 25
Tool (工具) 	DS 2.5 10	DS 3 10	DS 3 10