




SPE 2.5/3



SPE 2.5/4



SPE 4



Specifications (產品規格)	2.5 mm ²		2.5 mm ²		4 mm ²	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	c US AWG 12-28		c US AWG 12-28		c US AWG 12-28	
CSA	AWG 12-28		AWG 12-28		AWG 12-28	
IEC	0.2-2.5mm ²		0.2-2.5mm ²		0.2-4mm ²	
Insulating impulse voltage withstand / Pollution degree (額定衝擊電壓 / 污染等級)	8KV / 3		8KV / 3		8KV / 3	
Insulation stripping length(mm) (剝線長度)	8-9 mm		8-9mm		9-10mm	
Material/Available Color (材質顏色)						
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
For TS35x7.5	5 x 64 x 35.5		5 x 75 x 35.5		6 x 59 x 36.5	
For TS35x15	5 x 64 x 43		5 x 75 x 43		6 x 59 x 44	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板)	SEW35	50	SEW35	50	SEW35	50
End Plate (擋板)	SEP 2	50	SEP 3	50	SEP 4	50
Comb Link (連接式聯接件)	SQV 2.5/2	50	SQV 2.5/2	50	SQV 4/2	50
	SQV 2.5/3	50	SQV 2.5/3	50	SQV 4/3	50
MarkingTags (標記號)	W5 W5Z W5K	500	W5 W5Z W5K	500	W6 W6Z W6K	500
Tool (工具)	DS3		DS3		DS3	