




SPE 4/3










SPE 4/4



SPE 6



Specifications (產品規格)	4 mm ²		4 mm ²		6 mm ²	
Technical Data (技術參數)	Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size		Rated voltage/Rated current/Wire size	
UL	cUL ^{us} AWG 12-28		cUL ^{us} AWG 12-28		cUL ^{us} AWG 10-24	
CSA	AWG 12-28		AWG 12-28		AWG 10-24	
IEC	0.2~4mm ²		0.2~4mm ²		0.2~6mm ²	
Insulating impulse voltage withstand (額定衝擊電壓/Pollution degree /污染等級)	8KV / 3		8KV / 3		8KV / 3	
Insulation stripping length(mm) (剝線長度)	8-9 mm		9-10 mm		12-13 mm	
Material/Available Color (材質顏色)						
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
For TS35x7.5 	6 x 73.5 x 36.5		6 x 86 x 36.5		8 x 74.5 x 40	
For TS35x15 	6 x 73.5 x 44		6 x 86 x 44		8 x 74.5 x 47.5	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板) 	SEW35	50	SEW35	50	SEW35	50
End Plate (擋板) 	SEP 5	50	SEP 6	50	SEP 7	50
Comb Link (連接式聯接件) 	SQV 4/2	50	SQV 4/2	50	SQV 6/2	50
	SQV 4/3	50	SQV 4/3	50	SQV 6/3	50
MarkingTags (標記號) 	W6 W6Z W6K	500	W6 W6Z W6K	500	W6 W6Z W6K	500
Tool (工具) 	DS3		DS3		DS4	