





Features of Spring Clamp Terminal Blocks 彈片壓接型接線座



DSTTB 4-D



DST 2.5-MT-D



DST 4-MT-D



Specifications (產品規格)	2.5mm ²		2.5mm ²		4mm ²	
Technical Data (技術參數)	Rated voltage / Rated current / Wire Size		Rated voltage / Rated current / Wire Size		Rated voltage / Rated current / Wire Size	
UL	600V / 30A / AWG 28-10		600V / 16A / AWG 28-12		600V / 21A / AWG 28-10	
CSA	600V / 30A / AWG 28-10		600V / 16A / AWG 28-12		600V / 21A / AWG 28-10	
IEC	500V / 32A / 0.08-4mm ²		400V / 20A / 0.08-2.5mm ²		400V / 20A / 0.08-4mm ²	
Insulating Impulse voltage withstand / Pollution degree (額定衝擊電壓 / 污染等級)	6KV / 3		6KV / 3		6KV / 3	
Insulation stripping length (mm) (剝線長度)	10mm		10mm		10mm	
Material / Available Color (材質顏色)						
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)		T / W / H (mm)	
For TS35x 7.5	6.2 x 83.7 x 47.5		5.2 x 60.6 x 36.5		6.2 x 71.7 x 36.5	
For TS35x 15	6.2 x 83.7 x 55		5.2 x 60.6x 44		6.2 x 71.7 x 44	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板)	SEW35	50	SEW35	50	SEW35	50
End Plate (擋板)	DD-STTB4-D	50	DD-ST2.5/3-D	50	DD-ST4/3-D	50
Comb Link (連接式聯接件)	ODFBS2-6	50	ODFBS2-5	50	ODFBS2-6	50
	ODFBS3-6	50	ODFBS3-5	50	ODFBS3-6	50
	ODFBS4-6	50	ODFBS4-5	50	ODFBS4-6	50
	ODFBS5-6	50	ODFBS5-5	50	ODFBS5-6	50
	ODFBS10-6	10	ODFBS10-5	10	ODFBS10-6	10
Marking Tags (標記號)	DUC-TMF6	10 (側面 80 位)	DUC-TMF5	10 (側面 96 位)	DUC-TMF6	10 (側面 80 位)
	DUC-TM6	10 (正面 80 位)	DUC-TM5	10 (正面 96 位)	DUC-TM6	10 (正面 80 位)
Tool (工具)	DS3 (0.4 x 4.0mm)		DS3 (0.4 x 3.5mm)		DS3 (0.4 x 4.0mm)	