



Features of Spring Clamp Terminal Blocks 彈片壓接型接線座

DST 4-HEDI-D



DST 4-HESI-D



Specifications (產品規格)	4mm ²		4mm ²	
Technical Data (技術參數)	Rated voltage / Rated current / Wire Size		Rated voltage / Rated current / Wire Size	
UL	600V / 10A / AWG 28-10		600V / 10A / AWG 28-10	
CSA	600V / 10A / AWG 28-10		600V / 10A / AWG 28-10	
IEC	500V / 20A / 0.08-4mm ²		500V / 6.3A / 0.08-4mm ²	
Insulating Impulse voltage withstand / Pollution degree (額定衝擊電壓 / 污染等級)	6KV / 3		6KV / 3	
Insulation stripping length (mm) (剝線長度)	10mm		10mm	
Material / Available Color (材質顏色)				
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)	
For TS35x 7.5	6.2 x 61.6 x 65		6.2 x 61.6 x 65	
For TS35x 15	6.2 x 61.6 x 72.5		6.2 x 61.6 x 72.5	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.
End Bracket (終端擋板)	SEW35	50	SEW35	50
End Plate (擋板)				
Comb Link (連接式聯接件)	ODFBS2-6	50	ODFBS2-6	50
	ODFBS3-6	50	ODFBS3-6	50
	ODFBS4-6	50	ODFBS4-6	50
	ODFBS5-6	50	ODFBS5-6	50
	ODFBS10-6	10	ODFBS10-6	10
Marking Tags (標記號)	DUC-TMF6	10 (側面 80 位)	DUC-TMF6	10 (側面 80 位)
	DUC-TM6	10 (正面 80 位)	DUC-TM6	10 (正面 80 位)
Tool (工具)	DS3 (0.4 x 4.0mm)		DS3 (0.4 x 4.0mm)	