



Features of Spring Clamp Ground Terminal Blocks 彈片接地型接線座


DST 4/3-PE-D




CE




DST 4/4-PE-D




CE



DST 6-PE-D



CE



Specifications (產品規格)	4mm ²	4mm ²	6mm ²
Technical Data (技術參數)	Rated voltage / Rated current / Wire Size	Rated voltage / Rated current / Wire Size	Rated voltage / Rated current / Wire Size
UL	600V / AWG 28-10	600V / AWG 28-10	600V / AWG 24-8
CSA	600V / AWG 28-10	600V / AWG 28-10	600V / AWG 24-8
IEC	800V / 0.08-4mm ²	800V / 0.08-4mm ²	1000V / 0.2-6mm ²
Insulating Impulse voltage withstand / Pollution degree (額定衝擊電壓 / 汙染等級)	8KV / 3	8KV / 3	8KV / 3
Insulation stripping length (mm) (剝線長度)	10mm	10mm	12mm
Material / Available Color (材質顏色)			
Rail Dimensions (導軌尺寸)	T / W / H (mm)	T / W / H (mm)	T / W / H (mm)
For TS35x 7.5	6.2 x 71.7 x 36.5	6.2 x 87.3 x 36.5	8.2 x 69.5 x 43.5
For TS35x 15	6.2 x 71.7 x 44	6.2 x 87.3 x 44	8.2 x 69.5 x 51
Accessories (附件)	Cat. No. Qty.	Cat. No. Qty.	Cat. No. Qty.
End Bracket (終端擋板)	SEW35 50	SEW35 50	SEW35 50
End Plate (擋板)	DD-ST4/3-DP 50	DD-ST4/4-DP 50	DD-ST6-DP 50
Comb Link (選接式聯接件)	ODFBS2-6 50 ODFBS3-6 50 ODFBS4-6 50 ODFBS5-6 50 ODFBS10-6 10	ODFBS2-6 50 ODFBS3-6 50 ODFBS4-6 50 ODFBS5-6 50 ODFBS10-6 10	ODFBS2-8 50 ODFBS3-8 50 ODFBS4-8 50 ODFBS5-8 50 ODFBS10-8 10
Marking Tags (標記號)	DUC-TMF6 10 (側面 80 位) DUC-TM6 10 (正面 80 位)	DUC-TMF6 10 (側面 80 位) DUC-TM6 10 (正面 80 位)	DUC-TMF8 10 (側面 56 位) DUC-TM8 10 (正面 56 位)
Tool (工具)	DS3 (0.4 x 4.0mm)	DS3 (0.4 x 4.0mm)	DS4 (0.4 x 5.5mm)