



Features of Spring Clamp Ground Terminal Blocks 彈片接地型接線座



DST 16-PE-D



DST 16/3-PE-D



CE cULus



Specifications (產品規格)	16mm ²	16mm ²
Technical Data (技術參數)	Rated voltage / Rated current / Wire Size	Rated voltage / Rated current / Wire Size
UL	600V / AWG 24-4	600V / AWG 24-4
CSA	600V / AWG 24-4	600V / AWG 24-4
IEC	1000V / 0.2-16mm ²	1000V / 0.2-16mm ²
Insulating impulse voltage withstand / Pollution degree (額定衝擊電壓 / 汙染等級)	8KV / 3	8KV / 3
Insulation stripping length (mm) (剝線長度)	18mm	18mm
Material / Available Color (材質顏色)		
Rail Dimensions (導軌尺寸)	T / W / H (mm)	T / W / H (mm)
For TS35x 7.5	12.2 x 80.6 x 51.5	12.2 x 107.8 x 51.5
For TS35x 15	12.2 x 80.6 x 59	12.2 x 107.8 x 59
Accessories (附件)	Cat. No. Qty.	Cat. No. Qty.
End Bracket (終端擋板)	SEW35 50	SEW35 50
End Plate (擋板)	DD-ST16-DP 50	DD-ST16/3-DP 50
Comb Link (邊接式聯接件)	ODFBS2-12 10	ODFBS2-12 10
Marking Tags (標記號)	DUC-TMF12 10 (側面 40 位) DUC-TM12 10 (正面 40 位)	DUC-TMF12 10 (側面 40 位) DUC-TM12 10 (正面 40 位)
Tool (工具)	DS5 (0.4 x 6.5mm)	DS5 (0.4 x 6.5mm)