



Push In Spring Clamp Ground Terminal Blocks 推入式彈片接地型接線座


DPTTB 1.5-PE




CE cULus




DPTTB 2.5-PE




CE cULus



DPTTB 4-PE



CE cULus



Specifications (產品規格)	1.5mm ²	2.5mm ²	4mm ²
Technical Data (技術參數)	Rated voltage / Rated current / Wire Size	Rated voltage / Rated current / Wire Size	Rated voltage / Rated current / Wire Size
UL	600V / AWG 26-14	600V / AWG 28-12	600V / AWG 24-10
CSA	600V / AWG 26-14	600V / AWG 28-12	600V / AWG 24-10
IEC	500V / 0.14-1.5mm ²	800V / 0.08-2.5mm ²	800V / 0.2-6mm ²
Insulating Impulse voltage withstand / Pollution degree (額定衝擊電壓 / 污染等級)	6KV / 3	8KV / 3	8KV / 3
Insulation stripping length (mm) (剝線長度)	10mm	10mm	10mm
Material / Available Color (材質顏色)			
Rail Dimensions (導軌尺寸)	T / W / H (mm)	T / W / H (mm)	T / W / H (mm)
For TS35x 7.5	3.5 x 65.4 x 42.9	5.2 x 78.8 x 47.6	6.2 x 85 x 47.5
For TS35x 15	3.5 x 65.4 x 50.4	5.2 x 78.8 x 55.5	6.2 x 85 x 55
Accessories (附件)	Cat. No. Qty.	Cat. No. Qty.	Cat. No. Qty.
End Bracket (終端擋板)	SEW35 50	SEW35 50	SEW35 50
End Plate (擋板)	DD-PTTB1.5-DP 50	DD-PTTB2.5-DP 50	DD-PTTB4-DP 50
Comb Link (邊接式聯接件)	無	無	無
Marking Tags (標記號)	DUC-TMF3.5 10 (側面 144 位) DUC-TM3.5 10 (側面 144 位)	DUC-TMF5 10 (側面 96 位) DUC-TM5 10 (正面 96 位)	DUC-TMF6 10 (側面 80 位) DUC-TM6 10 (側面 80 位)
Tool (工具)	DS2 (0.4 x 2.0mm)	DS3 (0.4 x 3.5mm)	DS3 (0.4 x 3.5mm)