



COMBI Push In Type Plug In Connection 插拔式接線端




COMBI Push In Type Plug In Connection

DSPB 2.5/XP (X=1~15)



DPP-H2.5/XP



Specifications (產品規格)	2.5mm ²		2.5mm ²	
Technical Data (技術參數)	Rated voltage / Rated current / Wire Size		Rated voltage / Rated current / Wire Size	
UL	600V / 20A / AWG 28-12		600V / 20A / AWG 28-12	
CSA	600V / 20A / AWG 28-12		600V / 20A / AWG 28-12	
IEC	500V / 24A / 0.08-2.5mm ²		500V / 24A / 0.08-2.5mm ²	
Insulating Impulse voltage withstand / Pollution degree (額定衝擊電壓 / 污染等級)	6KV / 3		6KV / 3	
Insulation stripping length (mm) (剝線長度)	10mm		10mm	
Material / Available Color (材質顏色)	● ● ● ● ●		● ● ● ● ●	
Rail Dimensions (導軌尺寸)	T / W / H (mm)		T / W / H (mm)	
For TS35 x 7.5	X * 5.2 x 22.9 x 39.7		5.2 x 17 x 39.7	
Accessories (附件)	Cat. No.	Qty.	Cat. No.	Qty.
Snap-lock fitting Plate (鎖定片)	DPR2.5	50	DDPPH2.5	50
Comb Link (邊接式聯接件) 	ODFBS2-5	50	無	
	ODFBS3-5	50		
	ODFBS4-5	50		
	ODFBS5-5	50		
	ODFBS10-5	10		
Marking Tags (標記號) 	DUC-TMF5	10 (側面 96 位)	DUC-TMF5	10 (側面 96 位)
Tool (工具) 	DS3 (0.4 x 3.5mm)		DS3 (0.4 x 3.5mm)	