

MA126 PCB Terminal Block, Modular

MA



DIMENSIONS/POSITIONS

MA126-500M

| | | |
|--------|-------------------------|--------------------------|
| 間距 | Pitch | 5.00mm |
| 位數 | Poles | 2 ~ 3Poles |
| 塑膠本體 | Housing Material | PA 66 |
| 彈片 | Spring | Stainless Strip Steel |
| 端子 | Contact | Brass, Tin Plated |
| 螺紋 | Screw Thread | M2.6, Steel, Zinc Plated |
| 電線線徑 | Wire Size | 12 ~ 26AWG |
| 剝線長度 | Wire Strip Length | 5mm ~ 6mm |
| PCB孔徑 | PCB Hole Diameter | 1.3mm |
| 最大緊固扭矩 | Tightening Torque, Max. | 3.54 Lb-in |
| 環境作業溫度 | Operating Temperature | -40°C to +105°C |

TECHNICAL DATA

| | | |
|---|------|--|
| 連接符合標準 Connection in acc. with standard EN-VDE | | |
| 額定電流 I _n Nominal Current I _n | 15A | |
| 額定橫截面 Nominal Cross Section | - | |
| 最大負載電流 Maximum load current | 15A | |
| 絕緣材料 Insulating Material | PA | |
| 阻燃等級,符合UL94 Inflammability class acc. to UL94 | V0 | |
| 額定電壓,UL/CUL Nominal voltage, UL/CUL | 300V | |
| 額定電流,UL/CUL Nominal current, UL/CUL | 15A | |

