


MA321 PCB Terminal Block, Single Mold



MA

DIMENSIONS/POSITIONS

		MA321-500	MA321-100
間距	Pitch	5.00mm	10.00mm
位數	Poles	2 ~ 24Poles	2 ~ 14Poles
塑膠本體	Housing Material	PA 66	PA 66
彈片	Spring	Brass, Gold, Tin or Ni Plated	Stainless Steel
端子	Contact	Brass, Tin Plated	Brass, Ni Plated
螺紋	Screw Thread	M2.6, Steel, Zinc Plated	M2.6, Steel, Zinc Plated
電線線徑	Wire Size	14 ~ 26AWG	14 ~ 26AWG
剝線長度	Wire Strip Length	5mm ~ 6mm	5mm ~ 6mm
PCB孔徑	PCB Hole Diameter	1.4mm	1.4mm
最大緊固扭矩	Tightening Torque, Max.	4.0 Lb-in	3.0 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE		
額定電流 I_n	Nominal Current I_n	10A
額定橫截面	Nominal Cross Section	-
最大負載電流	Maximum load current	10A
絕緣材料	Insulating Material	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0
額定電壓,UL/CUL Nominal voltage, UL/CUL		300V
額定電流,UL/CUL Nominal current, UL/CUL		15A

