


MB102 PCB Terminal Block, Modular



MB

DIMENSIONS/POSITIONS

MB102-750M

| | | |
|--------|-------------------------|--------------------------|
| 間距 | Pitch | 7.50mm |
| 位數 | Poles | 1Poles |
| 塑膠本體 | Housing Material | PA 66 |
| 壓線圈 | Cage Clamp | Brass, Ni Plated |
| 端子 | Contact | Brass, Tin Plated |
| 螺紋 | Screw Thread | M3.0, Steel, Zinc Plated |
| 電線線徑 | Wire Size | 10 ~ 24AWG |
| 剝線長度 | Wire Strip Length | 6mm ~ 7mm |
| PCB孔徑 | PCB Hole Diameter | 1.3mm |
| 最大緊固扭矩 | Tightening Torque, Max. | 3.56 Lb-in |
| 環境作業溫度 | Operating Temperature | -40°C to +105°C |

TECHNICAL DATA

| | | |
|---|--|--------------------|
| 連接符合標準 Connection in acc. with standard EN-VDE | | |
| 額定電流 I_n Nominal Current I_n | | 30A |
| 額定橫截面 Nominal Cross Section | | 4.0mm ² |
| 最大負載電流 Maximum load current | | 30A |
| 絕緣材料 Insulating Material | | PA |
| 阻燃等級,符合UL94 Inflammability class acc. to UL94 | | V0 |
| 額定電壓,UL/CUL Nominal voltage, UL/CUL | | 300V |
| 額定電流,UL/CUL Nominal current, UL/CUL | | 30A |

